

## Industrial Chrome • Cylinder Manufacturing Hydraulic Component Rebuilding

ENVIRO-SAVE PRODUCTS INC. P.O. BOX 80129 7840 EIMONDS STREET BURNABY, B.C. V5H 3X5 OCTOBER 26TH, 1993

ATTENTION: KJELL KESSELL

HERE ARE THE RESULTS OF THE TESTING WE PERFORMED ON OUR DIESEL POWERED HYDRAULIC TEST STAND, BEFORE AND AFTER TREATING THE DIESEL AND HYDRAULIC OIL WITH ENVIRO SAVE PRODUCTS.

THE BEFORE AND AFTER TESTS WERE PERFORMED WITH THE SAME R.P.M. AND LOAD ON THE DIESEL AND HYDRAULIC SYSTEM.

## TEST RESULTS BEFORE AND AFTER TREATMENT.

	DECIBELS				TEMP INCREASE				
DIESEL:	1	BEFORE TREATMENT		AFTER TREATMENT	1	BEFORE TREATMENT	r ¦	AFTER TREATMENT	1
RUN @ 1100-1200 RPM FOR 1/2 HOUR	3 9	115	200	114	ì	(WATE 25 F	OR :	TEMP.) 15 F	1
TEST BENCH HYDRAULIC DRIVE PUMP - MOTOR - RUN @ 5000 PSI FOR 1/2 HOUR	1	115–116 116	1 1 2 2	113 112–113	1	(HYDRAULIC 35 F 35 F	0	1L TFMP.) 20 F 20 F	1 1 1

OUR TESTS INDICATE A REDUCTION IN NOISE AND A DEFINITE DECREASE IN THE AMOUNT OF HEAT GENERATED.

REGARDS,

COAST VALVE INDUSTRIES LTD.

RICK HUURMAN

7 - 10